

THE FIRECOMBO

TECHNICAL PARAMETERS

Amplla FIRECOMBO Fire Fighting Point

FIRE RATING:	SHIELD - TI62P4VSS / TI62P6VSS 21A, 113B, C / 34A, 183B, C
PRODUCT NAME:	HOSE REEL - ZH3025 BETA-02
SPECIFICATION:	Spray DN25
HOSE SPECIFICATION:	Stable
HOSE LENGTH:	30 m
HOSE DIAMETER:	25 mm
NOZZLE DIAMETER:	8 mm
REEL DIAMENTIONS:	580x600x210 mm
HANGING ELEMENT:	hinge
ALLOWABLE INLET PRESSURE:	2-12 bar
RECOMMENDED INLET PRES.:	4 bar
CERTIFIED ACCORDING TO:	EN 671-1: 2012
CERTIFICATE:	1038Xa/02
OVERALL DIAMENTIONS:	WALLBOX - WBC7128 710x710x300 mm
EMBEDDING DEPTH:	26 mm
BOX MATERIAL:	galvanized construction steel
BOX THICKNESS:	1 mm
REAR SUPPORT PLATE:	cement chipboard
THICKNESS OF SUP. PLATE:	10 mm
SHIELD HINGE:	steel/dural

