

THE HUSSECHUCK



TECHNICAL PARAMETERS

Ampla HUSSECHUCK Powder fire extinguisher

	TI62P4VSH	TI62P6VSH
FIRE RATING:	21A, 113B, C	34A, 183B, C
USE:	Solid materials, liquids, gases, live electrical equipment up to 1kV at the distance of 1m	Solid materials, liquids, gases, live electrical equipment up to 1kV at the distance of 1m
TOTAL WEIGHT:	~ 10.7 kg	~ 12.5 kg
OVERALL DIMENSIONS:	Diameter - 620 ±2 mm Width - 82 ±2 mm	Diameter - 620 ±2 mm Width - 82 ±2 mm
BODY VOLUME:	7.2 l	7.2 l
ALLOWABLE TEMP.:	-30°C / +60°C	-30°C / +60°C
EXTERNAL TREATMENT:	Powder painting red – RAL 3000	Powder painting red – RAL 3000
EXTINGUISHING AGENT:	Powder – Furex ABC Spezial (NH ₄) ₂ SO ₄ 68.5%, (NH ₄)H ₂ PO ₄ 21.5%	Powder – Furex ABC Spezial (NH ₄) ₂ SO ₄ 68.5%, (NH ₄)H ₂ PO ₄ 21.5%
WEIGHT OF EX. AGENT:	~ 4 kg	~ 6 kg
PROPELLANT:	Nitrogen N ₂ 100%	Nitrogen N ₂ 100%
DISCHARGE TIME:	14.1 ±2.1 s	19.6 ±2.9 s
BODY MATERIAL:	Alloy steel – P265GH	Alloy steel – P265GH
VALVE:	Chrome-plated brass – M45x1.5	Chrome-plated brass – M45x1.5
TRIGGER:	ABS – red	ABS – red
MAX. ALLOWABLE PRESSURE:	17 bar	17 bar
TEST PRESSURE:	25 bar	25 bar
CERTIFIED ACCORDING TO:	EN 3-7:2004+A1:2007 EN 3-8:2006/AC:2007 EN 3-10:2010	EN 3-7:2004+A1:2007 EN 3-8:2006/AC:2007 EN 3-10:2010
CERTIFICATE:	202-173-B-00512-22 1015-PED-B-00531-22	202-173-B-01277-22 1015-PED-B-01279-22